accuc@ld

ACR46GLCAL



31.5" x 19.5" x 22.75" (H x W x D)

Pharmacy Series ADA compliant 20" wide built-in undercounter all-refrigerator for vaccine storage, with stainless steel trimmed glass door, frost-free with an internal fan, external digital controls and NIST-calibrated thermometer, and lock

Highlights:

Less than 32" high to allow installation under lower ADA compliant counters

Specially designed to meet current CDC/VFC/VFA vaccine refrigeration guidelines for convenient storage in pharmacies and other healthcare facilities

High temperature alarm includes NIST calibrated external temperature readout (NIST certificate included)

Product Features:

Vaccine refrigerator	Purpose-built to meet the recommendations of the CDC, VFC and VFA for reliable vaccine storage	
ADA compliant	Sized just under 32" high to allow installation under lower ADA compliant counters	
Built-in capable	Front-breathing system allows the unit to be installed under cabinets with minimum clearance	
Slim 20" width	Full 2.65 cu.ft. capacity inside conveniently slim footprint	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
NIST calibrated external temperature display	y Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
Certificate of calibration included	Calibrated to NIST standards in our ISO/IEC 17025:2017 accredited laboratory, with a certificate included for your records	
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience	
Buffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines	



accuc@ld

ACR46GLCAL Specifications:

Height of Cabinet 24 5	" (81 cm)		
Height of Cabinet 31.5	" (80 cm)		
Nominal Width 20.0	" (51 cm)		
Width 19.5	" (50 cm)		
Nominal Depth 23.0	" (58 cm)		
Depth 22.75	" (58 cm)		
Depth with Handle 25.0	" (64 cm)		
Depth with door at 90° 41.0"	(104 cm)		
Capacity 2.65 cu	.ft. (75 L)		
Defrost Type F	rost-Free		
Door	Glass/SS		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	1.0		
Voltage/Frequency 115 V A	AC/60 Hz		
Weight 89.0 lbs	s. (40 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC 76110	1083902		
Refrigerator Features			
Door Swing	RHD		
Reversible	Yes		
Shelf Type	Wire		
Shelf Qty	3		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type Int	erior and Exterior		
Refrigerant Type	R600a		
Refrigerant Amount	0.99oz.		
High Side PSI	270.0		
Low Side PSI	105.0		
Level Legs Qty	4		
Interior Light	Yes		
Temperature Range	2º to 8ºC		
Dimensions			
Interior Height 21.25	" (54 cm)		

Interior Width	15.0" (38 cm)
Interior Depth	16.13" (41 cm)
Compressor Step Height	3.5" (9 cm)
Compressor Step Width	15.0" (38 cm)
Compressor Step Depth	4.75" (12 cm)



