# accucold

# ARG12ML



### **Product Features:**

#### 61.75" x 23.38" x 24.38" (H x W x D)

Performance series Med-Lab 12 cu.ft. upright glass door all-refrigerator, with antimicrobial silver-ion handle and hospital grade cord with 'green dot' plug

#### **Highlights:**

Intelligent microprocessor digital temperature controller


Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

| Purpose-built design                            | Designed and purpose-built to meet the demanding needs of scientific, life science, laboratory, and medical cold storage applications  |  |
|---|--|--|
| +/-1°C Variation                                | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |  |
| Antimicrobial silver ion-coated handle          | Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs   |  |
| Adjustable temperature                          | Intuitive controls let you adjust the interior temperature between +2 to +10°C   |  |
| Temperature alarm                               | Visual and audible alarms alert if the interior temperature rises or falls out of set range  |  |
| Remote alarm contacts                           | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)                     |  |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup   |  |
| Access port                                     | Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment   |  |
| Open door alarm                                 | Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)  |  |

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@accucold.com



## accucold

## **ARG12ML Specifications:**

| Overview                      |                     |  |  |
|-------------------------------|---------------------|--|--|
| Nominal Height                | 62.0" (157 cm)      |  |  |
| Height of Cabinet             | 61.75" (157 cm)     |  |  |
| Nominal Width                 | 24.0" (61 cm)       |  |  |
| Width                         | 23.38" (59 cm)      |  |  |
| Width with Door Open          | 23.88" (61 cm)      |  |  |
| Nominal Depth                 | 25.0" (64 cm)       |  |  |
| Depth                         | 24.38" (62 cm)      |  |  |
| Depth with Handle             | 26.13" (66 cm)      |  |  |
| Depth with door at 90°        | 46.5" (118 cm)      |  |  |
| Capacity                      | 12.0 cu.ft. (340 L) |  |  |
| Defrost Type                  | Automatic           |  |  |
| Door                          | Glass               |  |  |
| Cabinet                       | White               |  |  |
| US Electrical Safety          | ETL                 |  |  |
| Canadian Electrical<br>Safety | ETL-C               |  |  |
| Amps                          | 1.4                 |  |  |
| Voltage/Frequency             | 115 V AC/60 Hz      |  |  |
| Weight                        | 190.0 lbs. (86 kg)  |  |  |
| Parts & Labor Warranty        | 2 Years             |  |  |
| Compressor Warranty           | 5 Years             |  |  |
| UPC                           | 761101062709        |  |  |
| Refrigerator Features         |                     |  |  |
| Door Swing                    | RHD                 |  |  |
| Reversible                    | Yes                 |  |  |
| Shelf Type                    | Wire                |  |  |
| Shelf Qty                     | 7                   |  |  |
| Adjustable Shelves            | Yes                 |  |  |
| Thermostat Type               | Digital             |  |  |
| Fan Type                      | Interior            |  |  |
| Refrigerant Type              | R600a               |  |  |
| Refrigerant Amount            | 2.11oz.             |  |  |
| Interior Light                | Yes                 |  |  |
| Temperature Range             | 2 to 10ºC           |  |  |
| Dimensions                    |                     |  |  |
| Interior Height               | 53.0" (135 cm)      |  |  |
| Interior Width                | 20.0" (51 cm)       |  |  |
| Interior Depth                | 17.0" (43 cm)       |  |  |
|                               | . ,                 |  |  |

| Compressor Step Height | 6.5" (17 cm)  |
|------------------------|---------------|
| Compressor Step Width  | 20.0" (51 cm) |
| Compressor Step Depth  | 5.0" (13 cm)  |
|                        |               |

