## accuc@ld

# **ARS3PV**



34" x 18.5" x 19" (H x W x D)

Performance series Pharma-Vac 3 cu.ft. counter height allrefrigerator for vaccine storage with hospital grade cord with 'green dot' plug and antimicrobial silver-ion handle

### **Highlights:**

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Additional sensor reads interior air temperature for superior temperature control

#### **Product Features:**

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment
Open door alarm	Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)



## accuc@ld

### **ARS3PV Specifications:**

Overview			
Nominal Height	34.0" (86 cm)		
Height of Cabinet	34.0" (86 cm)		
Nominal Width	19.0" (48 cm)		
Width	18.5" (47 cm)		
Width with Door Open	19.0" (48 cm)		
Nominal Depth	19.0" (48 cm)		
Depth	19.0" (48 cm)		
Depth with Handle	20.75" (53 cm)		
Depth with door at 90°	36.0" (91 cm)		
Capacity	3.0 cu.ft. (85 L)		
Defrost Type	Automatic		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	0.6		
Voltage/Frequency	115 V AC/60 Hz		
Weight	85.0 lbs. (39 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101062532		
Refrigerator Features			
Door Swing	RHD		
Reversible	Yes		
Shelf Type	Wire		
Shelf Qty	4		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior		
Refrigerant Type	R600a		
Refrigerant Amount	1.06oz.		
Interior Light	Yes		
Temperature Range	2 to 8°C		
Dimensions			
Interior Height	28.38" (72 cm)		
Interior Width	15.25" (39 cm)		
Interior Depth	11.75" (30 cm)		
Compressor Step Height	8.0" (20 cm)		

Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	3.75" (10 cm)



