accucold

VT65MLVAC456ADA



32.38" x 23.63" x 23.5" (H x W x D)

Built-in undercounter ADA height -30°C all-freezer certified to NSF/ANSI 456 for vaccine storage, with NIST calibrated thermometer/alarm

Highlights:

Certified to NSF 456 for the storage of vaccines

Low temperature operation ideal for preserving certain pharmaceuticals

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Product Features:

Certified to NSF/ANSI 456 Vaccine Standard Designed and tested to comply with the new NSF vaccine storage standards through an independent laboratory

| Reliable temperature stability | Engineered to store vaccines and other select pharmaceuticals under stable temperature conditions | |
|---|---|--|
| Slim undercounter dimensions | 24" footprint is ideal for use under the counter | |
| ADA Compliant height | Sized at 32" high (32.38" to hinge cap) to fit under lower counters complying with ADA guidelines | |
| Built-in capable | Front-breathing design allows built-in installation under counters | |
| Low temperature operation | Preset and locked at -30°C to prevent accidental adjustments. Range can be adjusted between -15° and -35°C by contacting our technical support team | |
| Microprocessor control panel | Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience | |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range | |
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button | |
| ACCUCOLD DIVISION, FELIX STORCH, INC 770 Garrison Avenue Bronx, NY 10474 USA TEL 7 | | |

accucold

VT65MLVAC456ADA Specifications:

| Overview | |
|-------------------------------|--------------------|
| Nominal Height | 32.0" (81 cm) |
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.38" (82 cm) |
| Nominal Width | 24.0" (61 cm) |
| Width | 23.63" (60 cm) |
| Nominal Depth | 24.0" (61 cm) |
| Depth | 23.5" (60 cm) |
| Depth with Handle | 25.5" (65 cm) |
| Depth with door at 90° | 46.0" (117 cm) |
| Capacity | 1.85 cu.ft. (52 L) |
| Defrost Type | Manual |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S to NSF 456 |
| Amps | 1.3 |
| Weight | 105.0 lbs. (48 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101086903 |
| Freezer | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Interior Height | 24.25" (62 cm) |
| Interior Width | 17.63" (45 cm) |
| Interior Depth | 17.0" (43 cm) |
| Thermostat Type | Digital |
| Fan Type | Exterior |
| Refrigerant Type | R134a |
| Refrigerant Amount | 2.8 oz. |
| High Side PSI | 235.0 |
| Low Side PSI | 70.0 |
| Level Legs | 4 |
| Interior Drawers | Yes |
| Drawers Qty | 3 |
| Compressor Step Height | 5.5" (14 cm) |
| | . , |

| Compressor Step Width | 17.63" (45 cm) |
|-----------------------|----------------|
| Compressor Step Depth | 5.5" (14 cm) |
| Temperature Range | -15°C to -35°C |
| | |

_



