



MARKET FORGE

STERILMATIC STEAM STERILIZERS

The Largest Capacity in the Most Compact Space

Small on the outside, the Sterilmatics has as much inside capacity as many large, more costly conventional sterilizers and up to five times the capacity of smaller table top units.

Economical, reliable and simple to operate, the versatile Sterilmatics provides the highest standards of sterilizing performance in a number of facilities, such as, Laboratories, Veterinary Clinics, Food Processing Plants, Wineries, Fisheries, Dairy Processing Plants, and more.

Sterilize glass beakers, pipettes, test tubes and flasks. Metal and plastic instruments, syringes, needles, brushes, rubber gloves, catheters, rubber tubing, dressings, linens, petri dishes and more.

DIGITAL STERILIZER

Standard Features

- LCD display screen; monitor temperature, time and pressure
- Select temperature in °F (PSI) or °C (kPa)
- Sterilizing temps can range from 225°F (107°C) to 250°F (121°C)
- Choose from fast or slow exhaust
- Built-in data recorder and printer
- Programmable buttons to store up to 3 temp/time/venting cycle parameters
- Maintain a set temperature with a built-in microprocessor
- Electric steam trap
- Removable pan supports
- For use at altitudes up to 6500 ft
- 18-3/4" wide x 28-5/8" high x 31" deep (56-1/4" high on optional stand)



Digital Steam Sterilizers

MODEL	DESCRIPTION	PART NUMBER	APPROX. SHIPPING WT LBS/KG
STM-ED*	Digital sterilmatic (microprocessor controlled) with programmable time, temperature and venting (230°-250°F / 110°-121°C)	95-6300	150/68
STM-EDX**	Export model digital sterilmatic (microprocessor controlled) with programmable time, temperature and venting (230°-250°F / 110°-121°C)	95-6301	150/68

* These models are available in 208, or 240 Volts, 60Hz, 1 or 3 ph

** Export models are available in 220/380 Volts, 50Hz, 1 or 3 ph 4 wire or 240/415 Volts, 50Hz, 1 or 3 ph 4 wire

Adjustable feet are included as standard in all units.



Shown on optional
stand 95-6060



ANALOG STERILIZERS

Standard Features

- Automatic temperature controls
- Temperature up to 250°F (121°C)
- Thermostatic steam trap
- Thermometer range 180°-300°F (82°-149°C)
- 0-30 lb. steam gauge
- 0-60 minute timer
- Low water cut-off, signal light, and safety valve
- Flat perforated steam baffle
- Removable pan supports
- For use at altitudes up to 6500 ft
- 18-3/4" wide x 27-5/8" high x 31" deep
(55-1/4" high on optional stand)



Analog Steam Sterilizers

MODEL	DESCRIPTION	PART NUMBER	APPROX. SHIPPING Wt LBS/KG
STM-E*	Analog sterilmatic	95-2678	150/68
STM-EL*	Analog sterilmatic with adjustable temperature controls (230°-250°F)	95-3441	150/68
STM-EX**	Export model analog sterilmatic	95-2902	150/68
STM-ELX**	Export model analog sterilmatic with adjustable temperature controls (230°-250°F)	95-2903	150/68

* These models are available in 208, or 240 Volts, 60Hz, 1 or 3 ph

** Export models are available in 220/380 Volts, 50Hz, 1 or 3 ph 4 wire or 240/415 Volts, 50Hz, 1 or 3 ph 4 wire

Adjustable feet are included as standard in all units.

TERMS, CONDITIONS AND ORDERING INFORMATION

Orders are subject to ACCEPTANCE by Market Forge Home Office. ALL PRICES are subject to change without notice. Inspect merchandise immediately on receipt and notify carrier if SHIPMENT IS DAMAGED. All claims must be filed with carrier.


CANCELLED ORDERS and RETURN MERCHANDISE are subject to a restocking charge of 20% on domestic models and 30% on export (50Hz) models. Returned merchandise must be shipped prepaid after obtaining our written return authorization.

QUOTATIONS are subject to acceptance within 90 days. SHIPMENT must be within 6 months from date of order or quotation or may be subject to increase in price. Quotations will be submitted on request for delivery requirements beyond 6 months.

WARRANTY: 90 Days Labor, 1 Year Parts. NO EXTENDED WARRANTY!

FREIGHT CLASSIFICATION: 85

INTERNATIONAL ORDERS: Any orders outside the continental U.S. and Canada will be subject to an 8% Warranty Administration Fee added to the invoice and could be subject to other charges.



OPTIONS & ACCESSORIES

PART NUMBER	DESCRIPTION	APPROX. SHIPPING WT LBS/KG
95-6060	Stainless Steel Stand with Adjustable Shelf & Feet - 28" High*	23/10
95-6054	Extra Shelf (For Stand Listed Above)	4/1.8
10-1203	12" x 20" x 2-1/2" Perforated Tray (Unit will hold three of this size)	5/2.3
10-1204	12" x 20" x 4" Perforated Tray (Unit will hold (2) of these, as well as (1) - 2-1/2" tray)	6/2.7
10-1205	12" x 20" x 6" Perforated Tray (Unit will hold (1) of these, as well as (1) - 2-1/2" tray)	7/3.2
10-1228	12" x 20" x 2-1/2" - Wire Basket	4/1.8
10-1229	12" x 20" x 4" - Wire Basket	6/2.7
95-0436	Exhaust Condenser (Can't be connected to outside vent)	14/6.4
95-3629	Exhaust Condenser 240V, 50/60 Hz (Can be used with "Export" Sterilizers)	14/6.4
95-6061	Spare Parts Kit (STM-E & STM-EL Models)	N/A
95-6062	Spare Parts Kit (STM-EX & STM-ELX Models) Export	N/A
95-6233	Recording Thermometer (Provides Continuous 120 Volts / 60 Hz)	5/2.3
95-6234	Recording Thermometer (Provides Continuous 230 Volts / 50 Hz) Export	5/2.3
10-7933	Replacement 24 Hour Recording Chart (Fahrenheit)	1/.5
08-6244	Replacement 24 Hour Recording Chart (Celsius) Export	1/.5

* Sterilmatic overall height with stand is 55-1/4" (1403mm) for analog units and 56-1/4" (1429mm) for digital units

